Fagus-GreCon<br/>Greten GmbH & Co. KGP.O. Box 1243D-31042 Alfeld-HanoverPhone +49 (0) 5181-79-0Fax +49 (0) 5181-79-229E-Mail sales@grecon.comwww.grecon.com



GreCon Fire Protection





EN | R.03 | 2013.10 Subject to technical and country-specific modifications. © Fagus-GreCon Greten GmbH & Co. KG

# Spark Extinguishing Systems





#### Innovation is our Tradition.

With this maxim, we refer to our innovative company founder and my great-grandfather who founded the FAGUS shoe last factory in 1911. Even then he had the courage to engage the visionary, but unnoticed Walter Gropius, who became an internationally renowned architect, to build his factory, which today is regarded as the origin of the modern age building. UNESCO designated it as a World Cultural Heritage Site in 2011. With an extensive restoration, it is in very good condition, still in operation and owned by the family.

In 1970, our company experienced further innovation. My brother Gerd and I took over FAGUS, the shoe last production that continues operations today, and founded GreCon. Today, we are suppliers of measuring systems especially for the wood industry and fire protection systems worldwide. One of the fire protection systems is the spark extinguishing system.

In 1973, my father supplied a complete particleboard plant to Russia in which it burned several times a day. "You have to think of something" he said. We thought whether it was possible to detect sparks and to extinguish them before they cause fire or an explosion. The idea of a spark detection and extinguishment system was born.

#### We extinguish before you get burned.

Today, our spark detectors monitor industrial processes in about 200,000 installations around the world, not only in the woodworking industry, but also in many other production processes. This makes us proud, and it fills me with joy to see how many innovations have developed from our original idea!

Ernst Greten Managing Director of GreCon

## Why GreCon




- The GreCon spark extinguishing system was introduced as a world first for preventive fire protection in 1973
- Decades of **expert experience** in several industries
- About 200,000 installations **worldwide**
- Global service team with more than 80 service experts



### Your Benefit

- !
- Prevent ignition sources
- Avoid fire or explosions
- Avoid personal injuries and property damage
- Secure highest possible production availability



#### All Sensors at a Glance

There are different risks of fire and explosion in industrial processes. GreCon has suitable detectors for different risks.

#### Spark Detection Preferably in Dark Areas



Spark detectors FM 1/8 can be used in dark areas where ambient light is not present. This ensures the high sensitivity of the FM 1/8 sensors so that the detection of ignition sources can be optimised even in dense material flow. The optics of the sensors are normally kept clean by the air and material flow which makes the system easier to maintain.

#### Spark Detection in High-Temperature Areas

FM 3/8 sensors with fibre optic cables are used where processing or drying temperatures exceed 65 °C (149 °F). Three separate stainless steel covered glass fibre cables transmit the infrared radiation to the sensor, with each cable ending on a separate photo optic diode. Solid glass adapters are added to the cable end for extremely high temperatures. Detection reliability is achieved by using three detection elements per sensor. The fibre optic cables are available in different lengths for different duct diameters.





GreCon

GreCon can detect sparks on conveyor belts, production lines, or at transfer points between convevor systems.

A special sensor, type DLD 1/8, is used where ambient light is present.

#### Detection of Hot Particles and Glowing Embers

Industrial production processes often create hot materials or hot large masses without them glowing in a visible range. Such materials are, for example, coaly or sooty deposits within ducts or high volumes of comminution processes. They occur in exhaust ducts of hardening shops or foundries as well as in recycling plants. The HPD detector reliably detects dangerous potentials in this low, non-glowing temperature range.

#### Temperature Monitoring of Facilities

Thermo detectors TM 1/9 not only react when exceeding the set temperature threshold, but give an alarm upon fire-typical temperature rises. The thermo-element has two different trigger functions that work in parallel. In case of smouldering fire, i.e. slowly rising temperatures, the system heats up steadily and triggers an alarm when the nominal value of the sensor is reached. In case of quickly rising temperatures, typical of fuel fire, an alarm is triggered before the nominal value is reached.

#### Detection of Smouldering and Other Fire

Burning embers deeply hidden in the material release combustion gases. These gases can be detected - e.g. in a silo - by a combustion gas detector BGM. Combustion gas detectors can be used as stand-alone devices or in combination to monitor large areas. Smouldering fire is detected by the released gases CO. H2. KW (phenolic hydrocarbon or nitrogen) in a ppm range. For that, the combustion gas detectors have to be installed in the area in which smouldering gases can spread. This makes fire detection possible before the gases ignite.

#### **Detection of Open Flames**



GreCon flame detectors use modern UV/IR technology for reliable detection of flames.

The UV sensor gives early alarm in case of arising fire, thus allowing early manual extinguishment.

If the fire continues to spread, the independent IR sensor will confirm the UV alarm, thus allowing reliable automatic extinguishment.

#### **Detection of Smoke**



Scattered light smoke detectors SRM 1/8 detect fires that develop smoke, e.g. in return-air ducts of dust filters. Scattered light smoke detectors can be used to detect fire in dustfree areas.


#### Sensor Accessories




Additional Measures against Heavy **Dirt Accumulation** 

If dirt accumulation or other build-up on the sensor optics is expected, special air purge adapters increase the detection reliability. Cleaning intervals are thus extended.

#### **Light Intrusion**





Light intrusion, whether artificial or daylight, might have a negative effect on the infrared radition detection in the sense of the application. Slotted diaphragms are used to avoid false alarms and to op-



#### Countermeasures at a Glance

To achieve a preventive fire and explosion protection effect, automatic countermeasures are used in connection with detection.





The new **ultrahigh-speed extinguishment UHS** consists of a special high-speed solenoid valve as well as special spray nozzles that are adapted to this system. GreCon now offers a solution for those areas of short pipe distances.

With the ultrahigh-speed technology, extinguishing distances of less than 2 m become possible.

#### **Diversion of Material Flow**

**Diversion gates** can divert the material flow to prevent the transfer of ignition sources to other plant areas. Diversion gates are also available in stainless steel for applications in the food and other industries.

#### Interruption of Material Flow

Fire traps and shut-off gates are accessory parts which can mechanically close transport ducts to prevent the transfer of ignition sources to other plant areas. Fire traps and shut-off gates are also available in stainless steel for applications in the food and other industries.

#### **Alternative Extinguishing Concepts**

On demand, **special application-specific extinguishing concepts** with gas, foam or steam can be used in connection with our system.

#### Accessories

#### Pressure Increasing Units

If the available water flow pressure for extinguishment is inadequate, a water pressure increasing unit is installed to create the required water pressure. If the water flow rate to the pressure increasing pump is too low, or, if the unit is connected to a drinking water supply, a storage tank must also be installed.



#### **Anti-Freeze Protection**

Heat tape and insulating material can be used to **protect water pipes** and extinguishing devices from freezing in areas exposed to frost. We offer special, easy to maintain insulating bags for the extinguishing devices.





#### A fine water mist spray emerges from the **extinguishing nozzles** within a few milliseconds and is used for extinguishing ignition sources. They are made of high-quality stainless steel, which increases the resistance to wear. After extinguishment, the shutter cone of the nozzle automatically seals it and keeps it free of contamination. Using different nozzle types minimises the necessary water quantity.





#### Multi-Touch Panels for Fast and Easy Operation of Spark Extinguishing Systems

The new 10" colour display with multi-touch function enables you to quickly call up desired information in a self-explaining and compact way from different levels of the GreCon control console. Thus, it will be quite easy to have all information available. Not only data that is available quickly after an alarm, but also long-term information from deeper levels can be shown on the display. The possibility to represent complete flowsheets is especially emphasised. Areas that have current alarms can be examined more closely by using the simple zoom function.

#### Important Information Available Quickly

Important data can be displayed quickly by direct selection of information via clear symbols. The display memory offers room to store electronic files, such as instruction and operating manuals, which can be used when a paper printout is not available.

#### Easily Retrofit Existing Systems

In many cases, the ease of operations of the multitouch display can replace the existing standard GreCon control console display.

### Operation Panel for Small Control Consoles

Small GreCon control consoles are equipped with standard operation panels.




The new multi-touch display for easy and intuitive operation

- 🛛 👲		9 9 9	ы <mark>ы</mark> ы		_		1923
and an end	C argentes mate	12 Jacob state to a feature	Last free nationer in R In second 2	and the second is 8 from 1	-		LET Ave have not 1 in a rate of 2
Last from taxons such in some			All the role is an a lange start		a last a state of the second	The second states	Charge service die aus
and research to the last		and or point raises.	all star or greater	and the second second second	All of passes a de-		and other that
C period in the second	1002100-000	and onlines to be written	and the second	All other had unlike with the little		188 () and she	and it was also
second astronom	All & weather	The set of	The second second second	214 S. D. and place	and a set of a	-	(10) It was after upto
Concession of	Last C and other par-		100.000-000	altheorem .			1010.000.000.000
Add from particular And a	Carl and the second	100308-108	al persent to	the second site	These seattle period		
International International	THE I will don't	STEL - HE PART		the basher (	terine	a to deal add	and the second second
-		-		Ref (State)			

BS 7 NET makes clear operation and control from the control station possible

#### BS 7 NET System Survey



#### BS 7 NET for Easy and Clear Handling

BS 7 NET allows local installation of control consoles of the CC 7000 and CC 5000 series on the company premises, e.g. in control rooms. No space is required in control stations, and cable distances can be reduced to a minimum. The decentralised architecture provides additional redundancy and increases easy maintenance of the entire system. The control console can be placed even closer to production.

BS 7 NET is a simple operation and visualisation possibility of the current incidents in the system. The operation staff can react to current alarm incidents much faster. The easy handling can simplify the operation of spark detection and extinguishment systems in daily life.

Essential operation are, for example, the acknowledgement of alarms or the clear administration of disablings. The BS 7 NET server collects all information and communicates with the control consoles and the operation clients that might be installed in different production sections. One can see at a glance where danger zones are concentrated and whether interventions are necessary.

BS 7 NET displays alarm frequencies and records the events of all control consoles with a time stamp exactly to the millisecond. Management and operator are always up to date.

Data can be exchanged with the customer's control systems via gateways to Profibus, Profinet or DeviceNet.





